

TECHNICAL DATA

Cooling capacity R404A/507 (te= -8°C ; DT1=8K):	5,30 kW
Cooling capacity R404A/507 (te= 0°C ; DT1=10K):	7,80 kW
Exchange surface:	22,0 m ²
Tube volume:	6,0 dm ³
Air flow:	4113 m ³ /h
Air throw:	10 m
Gas coil connection:	22 Ø mm
Liquid coil connection:	1/2 Ø cal
Weight:	45 kg

FANS

Diameter:	300 Ø mm
Number of fans:	3
Voltage:	230/50 V/Hz
Power:	204 W
Current:	1,49 A

ELECTRIC DEFROST


Voltage:	230/50 V/Hz
Coil block:	2x1200 W
Drip tray:	2x1200 W
Total:	4800 W

THE CORRECTION FACTORS


Tevap.[°C] / DT1[K]	13	12	11	10	9	8	7	6	5
5	-	2,126	1,884	1,575	1421	1,330	1,191	1,033	0,981
4	-	2,060	1,818	1,541	1,410	1,303	1,156	0,995	0,853
3	2,233	1,956	1,783	1,525	1,395	1,281	1,123	0,969	0,827
2	2,164	1,948	1,749	1,510	1,371	1,242	1,095	0,935	0,793
1	2,129	1,921	1,714	1,498	1,336	1,211	1,065	0,908	0,766
0	2,110	1,911	1,662	1,488	1,316	1,176	1,036	0,877	0,735
-5	1,796	1,657	1,449	1,389	1,235	1,099	0,962	0,826	0,690
-8	1,623	1,529	1,344	1,250	1,124	1,000	0,877	0,752	0,625
-10	1,551	1,462	1,304	1,238	1,114	0,992	0,868	0,743	0,619
-15	-	1,319	1,280	1,208	1,089	0,967	0,846	0,724	0,604
-20	-	1,200	1,259	1,179	1,062	0,942	0,825	0,706	0,589
-25	-	-	1,042	1,145	1,035	0,915	0,804	0,688	0,574
-30	-	-	-	1,114	1,008	0,891	0,780	0,671	0,559
-35	-	-	-	1,094	0,986	0,874	0,766	0,656	0,546

DIMENSIONS

A:	814 mm
B:	295 mm
C:	1533 mm
D:	766 mm
E:	734 mm
F:	1220 mm



SAMPLE PICTURES



Pictures of some products may vary. Every effort was made to information contained in this catalog are correct. Due to the constant technological developments reserves the right to make changes without notice.